


For reference only. See data sheet for the detailed specifications.

Technical Specification



EIA WR	WR75
Frequency Range(GHz)	11.0 – 14.0
Bandwidth	Full
Common Port	21.5mm/ 0.846" Circular WG
Insertion Loss(dB)	0.5 Max
VSWR	1.5:1 Typ.
Cross Pol. Isolation(dB)	55 Typ. ; 45 Min.
Port to Port Isolation(dB)	30 Min.
Common Port Flange	FBP120(UBR120)
Flange	FBP120(UBR120)
Material	Al
Size(mm)	146.5 x 38 x 40.7
N.W.(Kg)	0.22 Around

Outline Drawing (Size: mm)



AINFO Inc.


China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA: Tel: (+1) 949-639-9688,

Page 1 of 5


(+86) 10-6266-7327 Fax: (+86) 10-6266-7379
(+86) 28-8519-3044 Fax: (+86) 28-8519-3068
(+1) 949-639-9608 Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)



FBP120



FBP120-M

AINFO Inc.

China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA: Tel: (+1) 949-639-9688,


Page 2 of 5

(+86) 10-6266-7327 Fax: (+86) 10-6266-7379
(+86) 28-8519-3044 Fax: (+86) 28-8519-3068
(+1) 949-639-9608 Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results


Port H_ Insertion Loss(Test with two OMT back to back)




Port V_ Insertion Loss(Test with two OMT back to back)




Port H_VSWR



Port V_VSWR



Cross Polarization Isolation



Port to Port Isolation

