





For reference only. See data sheet for the detailed specifications.

Technical Specification



Freq. Range(GHz)	18.0 - 40.0
Coupling(dB)	10
Coupling Accuracy(dB)	±0.7 Max.
Directivity(dB)	12 Min.
Insertion Loss(dB)	1.5 Max. (Not including the theoretical loss 0.46dB)
Mainline VSWR	1.7:1 Max.
Coupled VSWR	1.7:1 Max.
Average Power(W CW)	20 Max.
Peak Power(KW)	3
Connectors	2.92mm-Female
Operating Temp.(°C)	-55 ~ +85
Material	Al
Finish	Chemical Conversion Coating, Black Paint
Size(mm)	31.8 x 12.8 x 15.5
Net Weight(Kg)	0.04 Around

Outline Drawing (Size: mm)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608


Page 1 of 3

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results

Coupling



Directivity



Insertion Loss (Including the theoretical loss 0.46dB) & VSWR

CH1 S11 SWR 7.00 m / REF 1 5: 1.8432 35.820 000 000 GHz
CH2 S21 LOG 1.5 dB / REF - .46 dB 5: - .80500 dB 19.980 000 000 GHz
CH4 S22 SWR 7.00 m / REF 1 5: 1.2153 35.380 000 000 GHz

