


For reference only. See data sheet for the detailed specifications.

Technical Specification







EIA WRD	WRD650
Frequency Range(GHz)	6.5 – 18.0
Insertion Loss(dB)	0.3 Max.
VSWR	1.50:1 Max.
Flange	FPWRD650D28
Connector	N-Female
Average Power(W CW)	400 Max.
Peak Power(KW)	1
Material	Cu
Size(mm)	55.8 x 35 x 35
Net Weight(Kg)	0.19 Around

PATENT ID (China)

ZL202222525193.5, ZL202230631554.7

Outline Drawing (Size: mm)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608


Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)


FPWRD650D28

(With two through mounting holes
and two screws holes)



Test Results

I. L. (Test with two adapters back to back)



VSWR

